

Autoclavable Bottle-top Dispenser

DISPET EXII

- Autoclavable. (121°C for 20 minutes)
- 3 sized adapters for fitting with various types of bottles.
- Chemical-guard materials used for liquid contact parts.
- Adjustable Inlet tube for various types of bottles.
- Liquid returning mechanism for minimizing the waste of reagents.
- The wetted parts are chemically resistant.
Borosilicate glass, fluorocarbon polymers, Ceramic, Platinum-Iridium

121°C
20min
Autoclavable
γ-ray irradiation
50kGy



Specifications

Cat. No	Volume range (mL)	Increment (mL)	Accuracy (%)	Precision (%)	Thread	Attached adapters
00-DPX2-20	0.2 – 2.0	0.05	±0.5	≤0.1	GL-45	GL-28, GL-32, GL-38
00-DPX2-50	0.5 – 5.0	0.1	±0.5	≤0.1		
00-DPX2-100	1.0 – 10.0	0.2	±0.5	≤0.1		
00-DPX2-250	2.5 – 25.0	0.5	±0.5	≤0.1		
00-DPX2-500	5.0 – 50.0	1	±0.5	≤0.1		
00-DPX2-1000	10.0 – 100.0	2	±0.5	≤0.1		

Adapter

Cat. No	Size	Cat. No	Size
00-DPX-003A	32 / 28mm	00-DPX-003C	45 / 38mm
00-DPX-003B	45 / 32mm	00-DPX-003D	45 / 40mm

*Numbers right side of '/' are caliber size of the bottles.

Bottle-top Dispenser

DISPET Mini

- Suitable for repetitively micro volume dispensing.
- Light and compact model for easy-to-carry-out.
- Chemical-guard materials used for liquid contact parts.
- The wetted parts are chemically resistant.
Borosilicate glass, fluorocarbon polymers, Platinum-Iridium
- *Bottles are available as optional parts.



Specifications

Cat. No	Volume range (μL)	Accuracy (%)	Precision (%)	Thread
00-DPM-250	100 / 250	±2.0	≤0.4	GL-28
00-DPM-1000	500 / 1000	±1.0	≤0.2	GL-28
00-DPM-2000	1000 / 2000	±1.0	≤0.2	GL-28