Autoclavable Micro Pipette

Nichipet[®] Premium



5years warranty is proof of high durability.



What's new!







- ■Hand temperature doesn't permeate through the body of the pipette which works to avoid affecting volume measurement. (Patented)
- *All features of Nichipet EXII are available on Nichipet Premium.
- Since the volume indicator is made of glass, ultraviolet germicidal of the clean bench will not make it cloud.
- From prolonged irradiation, the surface layer of plastic may deteriorate or discolor, but its performance is not affected.

Specifications

Cat. No	Volume Setting	Volume range(µL)	Increments(µL)	Usable tips		
00-NPP-2	Digital Setting	0.1 – 2	0.002	BMT2-UT/UTWR/UTWRB、FUT/FUTRB		
00-NPP-10		0.5 – 10	0.01	BMT2-SSW/SSWR/SSWRB、FSS/FSSRB		
00-NPP-20		2-20	0.02	BMT2-SG/SGR/SGRB、FSG/FSGRB		
00-NPP-100		10 – 100	0.1	BMT2-SG/SGR/SGRB、FSE/FSERB		
00-NPP-200		20 – 200	0.2	BMT2-SG/SGR/SGRB、FAG/FAGRB		
00-NPP-1000		100 – 1000	1	BMT2-LG/LGR/LGRB、FLG/FLGRB		
00-NPP-5000		1000 – 5000	10	BMT2-X/XR/XRB		
00-NPP-10000		1000 – 10000	10	BMT2-Z/ZR/ZRB		

^{*}See p.19-20 for tip selection.

Accuracy and Precision

Cat. No	Volume(μL)	Accuracy(%)	Precision(%)	Cat. No	Volume(µL)	Accuracy(%)	Precision(%)
00-NPP-2	0.2	±12.0*	≦6.0*	00-NPP-200	20	±1.0	≦0.5
	1	±5.0	≦2.5		100	±0.8	≦0.3
	2	±3.0	≦1.0		200	±0.8	≦0.2
00-NPP-10	1	±4.0	≦3.0	00-NPP-1000	100	±1.0	≦0.5
	5	±1.0	≦1.0		500	±0.8	≦0.3
	10	±1.0	≦0.5		1000	±0.7	≦0.2
00-NPP-20	2	±5.0	≦3.0	00-NPP-5000	1000	±1.0	≦0.3
	10	±1.0	≦1.0		2500	±0.8	≦0.3
	20	±1.0	≦0.4		5000	±0.6	≦0.2
00-NPP-100	10	±2.0	≦1.0	00-NPP-10000	1000	±2.0	≦0.4
	50	±1.0	≦0.3		5000	±0.8	≦0.3
	100	±0.8	≦0.3		10000	±0.4	≦0.2

Nichiryo's quality starter packages

Nichipet Premium S-PAC

- Package type of 3 selected Pipettes with racked -Tips.
- Ready-to-start packages with 3 sizes of pipettes to perform high AC and CV pipetting.
- ■3 packages are available to cover wide range of volume.





3 pcs

Racked Tip 3 or 4 racks

3 pcs



Nichiryo Tube Opener (code:00-NTO)

"Easier" and "safer" to open tube lid with holding pipette



- ■Attached on grip end, 0.5, 1.5 mL tube and screw cap can be opened easily.
- *Compatible with Nichipet Premium (2-1000µL) and Nichipet EXII (2-1000µL)

Nichipet Premium S-PAC

Description	Cat. No	Content
Nichipet Premium S-PAC A	00-SP-AP	NPP-10, NPP-100, NPP-1000 BMT2-SSWR(0.5~10 μ L), BMT2-SGR(2~200 μ L), BMT2-LGR(100~1000 μ L), NTO
Nichipet Premium S-PAC B	00-SP-BP	NPP-20NPP-1000 BMT2-SGR(2 \sim 200 μ L) \times 2BMT2-LGR(100 \sim 1000 μ L) NTO
Nichipet Premium S-PAC H	00-SP-HP	NPP-2,NPP-10,NPP-100 BMT2-UTWR(0.1~10 μ L) \times 2, BMT2-SSWR(0.5~10 μ L) , BMT2-SGR(2~200 μ L) , NTO

^{*}The AC and CV above are measured with the disposable tips described in the catalogue.

*The AC and CV at 0.2µL depend much on the sampling skill and the sampling condition where pipettes are used.